







DAMPA MARINE CEILINGS PROVIDING SAFETY ON BOARD

DAMPA has produced and delivered metal ceilings to many of the world's largest and most prestigious passenger vessels and cruise liners, navy applications, traditional merchant ships, offshore accommodation platforms and the larger high-speed aluminium and carbon composite crafts.

DAMPA's Marine activities were founded early 1970's following a fire protection development project within the IMO framework.

In 1972 the DAMPA Continuous Ceiling System was launched – the *first* marine ceiling according to a new continuous class principle of fire protection to be incorporated in the International Safety of Life at Sea regulation, SOLAS-74.

DAMPA hereafter quickly became widely acknowledged as the international trendsetter gaining approvals and certifications from leading National Authorities and Classification Societies Worldwide.

DAMPA Marine Ceilings provide a safe and pleasant environment at sea, thanks to the high safety classification and the exceptional acoustic performance and superior appearance.

DAMPA's Quality Management System is according to DS/EN ISO 9001:2008 ensuring that all DAMPA Marine Ceiling Systems are manufactured to the highest standards, within close tolerances to guarantee an accurate, fast and reliable installation.

www.dampa.com

LOGISTICS

INTEGRATION

SAFETY ON BOARD

QUALITY

TECHNIQUE











DAMPA PANEL DCC 300

The B-15 fire rated ceiling system DAMPA DCC 300 consists of linear ceiling panels in a standard modular width of 300 mm. By use of only a few basic components a functional and aesthetically pleasing ceiling can be designed to suit a range of applications and areas.

The DCC 300 ceiling panels are made from stove-enamelled 0.6/0.5 mm galvanised steel respectively. The panels can be supplied perforated or plain, and in any specified length, from 600 to 5000 mm as standard. Lengths less than 600, and up to 6000 mm can be made to order. All panels are 26 mm deep and are supplied with end closings and 25 mm mineral wool inlay as standard. Room-to-room sound reduction of 41 dB - 44 dB depending on type of insulation inlay, and from 46 dB - 50 dB depending on type of additional insulation overlay.

The DAMPA DCC 300 Ceiling System has, with only minor modification of the Basic Installation Principle, been successfully tested with g forces up to 175 by the Danish and US Navies.





DAMPA DCC 3000

DAMPA DCC 3000 allows for a flat, continuous surface to the ceiling area due to the tight joint, and snug fit between the panels. The panels are installed from underneath the perimeter supports, thus maximising the available space within the ceiling void.

No suspension points nor time consuming installation of additional components are required in areas of up to 3000 mm widths. All panels are supplied with end-closings and 20 mm mineral wool inlay as standard.

DAMPA INTERVAL

DAMPA Interval adds a minimalistic expression to the ceiling. The open area between the panels is variable, allowing for a greater scop in relation to design, functionality and appearance of the ceiling. DAMPA Interval can be produced in varied dimensions as desired or required by the individual project.









DAMPA TILES

Consists of various types of tiles in many configurations with different function and architectural expressions, available both in aluminium and steel

DAMPA Tiles with Bevelled Edge along all edges emphasises the rectangular feature of the ceiling.

DAMPA Tiles with Square Edge are distinctly flat to form one large neutral ceiling area.

DAMPA "Rainfall Ventilation" Tiles with Bevelled Edge and with Square Edge can be installed with a gap of variable size crosswise to the carrier for air injection in areas, where the ceiling void is used as air supply chamber.

Standard dimensions of the tiles are 600x600 or 300x300 mm. Additionally DAMPA offers delivery of the well-known Clip-in Tiles in steel in new practical dimensions, for example 300x1200 mm, 300x1500 mm or 600x1200 mm.





DAMPA 100/200/300

These panels consists of different modular units which can be installed on the same modular carrier in any combination offering numerous possible design and functional applications. DAMPA 100 ceiling units are as standard, supplied without end closing, whereas DAMPA 200/300 ceiling units are end closed. Approved as C-class material by leading classification societies, national and safety administrations.



DAMPA 600 HOOK-ON

B-15/A-30 self supporting Hook-On Ceiling System is designed specially for corridors. Each full sized panel can swing down separately. This gives an unlimited access to above services anywhere without disturbing the fire integrity of the ceiling. No additional insulation is required. The ceiling joint ensures a tight, uniform "pencil" line connection with all panels in flat alignment forming a distinctively plane and neutral ceiling area. Widths of 300 or 600 mm and lengths up to 1435 mm are available.



TECHNICAL SOLUTIONS AND SUPPORT

All the way through the project phase from the design phase to finished product, we supply with consultancy combining the expertise of our own engineers completing detailed drawings of your project with the support from our experiensed marine customer service team.

Fast and efficient installation is assured, as ceiling panels are supplied 'pre-cut' in accordance with customer drawings and specifications.

All ceiling panels are precut to fit actual room dimensions. Factory manufactured start, end, stepped and diagonal panels and cut outs for luminaires, spot lights, speaker panels, smoke detectors, etc.

CERTIFICATES AND APPROVALS

DAMPA's products are continuously tested according to international requirements, such as fire stability and integrity. Certificates and approvals from leading classification societies have been achieved.

CE-mark of Conformity
IMO and SOLAS Requirements
Non-Toxicity and Calorific Value
EEA Marine Equipment Directive 96/98 EC



DESIGN AND INSPIRATION

Metal's inherant flexibility means that the sky is the limit for your ceiling design. Whether you are working in steel or aluminium, there is an endless array of options available at your disposal, ranging from design, through to dimensions and surfaces. DAMPA has more than 3,000 international marine references for inspiration to draw on.

ACOUSTICS

DAMPA's metal ceilings ensure an exceptional acoustic environment, adjustable to varying demands on reverberation times.

To reduce the general sound level the perforated ceilings units are the most effective solution.

IDENTIFICATION AND HANDLING ON SITE

DAMPA meets your specific requirements of packaging. DAMPA Panels are as standard supplied in pre-cut length according to specification to suit actual room dimensions. Identification and Handling on Site Ceiling unit boxes are labelled with contents, ceiling unit length as well as deck and room number for easy identification and handling on site.

REFERENCES

Front:

DAMPA DCC 300 Wheelhouse - Breakaway, Meyer Werft, Germany 1. DAMPA DCC 300 - Wheelhouse - Celebrity Solstice, Meyer Werft, Germany

DAMPA DCC 300 - Oceanview Café - Celebrity Eclipse, Meyer Werft, Germany
 DAMPA DCC 300 - Ladies Room - Celebrity Solstice, Meyer Werft, Germany

4. DAMPA DCC 300 - Carridor - Breakaway, Meyer Werft, Germany

5. DAMPA DCC 3000 - Cabin - AIDA Sol, Meyer Werft, Germany

DAMPA DCC 3000 - Hospital - AIDA Mar, Meyer Werft, Germany
 DAMPA Clip-in Tiles - Euroferries Pacifica, Austal Ships, Australia

8. DAMPA Clip-in Tiles - Champagne Bar - Queen Mary 2 - Chantiers de la Atlantique, France

9. DAMPA Clip-in Tiles - Art Gallery - Celebrity Solstice, Meyer Werft, Germany

10.DAMPA Clip-in Tiles / DAMPA DCC 300 - A-Suite - Celebrity Solstice, Meyer Werft, Germany



Telephone: +61 (0) 8 9302 5777
PO B

sales@ceilingworks.com.au www.ceilingworks.com.au